

AMENDMENTS TO CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

Claims 1-12 (canceled)

Claim 13. (Currently Amended) A receiving modem that is configured to perform transmission and reception of signals with a transmitting modem, the receiving modem ~~comprising;~~ comprising:

a ~~transmitter~~ transmitter that is configured to transmit a facsimile control signal;

a detector that is configured to detect a response signal to the facsimile control signal transmitted from the transmitting modem;

a controller that is configured to communicate with the transmitting modem based on the communication procedure specified in ITU Recommendation V.8, when a CM signal is detected as the response signal, and to data communicate with the transmitting modem, when a signal used in data communication is detected as the response signal.

Claim 14. (Previously Presented) The receiving modem according to claim 13, wherein the facsimile control signal is a DIS signal specified in ITU Recommendation T.30, and the controller executes data communications with the transmitting modem based on the data communication procedure specified in ITU Recommendation V.22, when a SI signal is detected as the response signal.

Claim 15. (Previously Presented) The receiving modem according to claim 13, wherein the facsimile control signal is a DIS signal specified in ITU Recommendation

T.30, and the controller executes data communication with the transmitting modem based on the data communication procedure specified in ITU Recommendation V.32, when an AA signal is detected as the response signal.

Claim 16. (Currently Amended) A receiving modem that is configured to perform transmission and reception of signals with a transmitting modem, the receiving modem ~~comprising;~~ comprising:

a ~~transmitter~~ transmitter that is configured to transmit a data communication signal;

a detector that is configured to detect a response signal to the data communication signal transmitted from the transmitting modem;

a controller that is configured to communicate with the transmitting modem based on the communication procedure specified in ITU Recommendation V.8, when a CM signal is detected as the response signal.

Claim 17. (Previously Presented) The modem according to claim 16, wherein the data communication signal is an AC signal specified in at least one of ITU Recommendation V.22 and V.23.

Claim 18. (Currently Amended) A communication control apparatus provided with a receiving modem that is configured to perform ~~to~~ transmission and reception of signals with a transmitting modem, the receiving modem ~~comprising;~~ comprising:

a ~~transmitter~~ transmitter that is configured to transmit a facsimile control signal;

a detector that is configured to detect a response signal to the facsimile control signal transmitted from said transmitting modem;

a controller that is configured to communicate with the transmitting modem based on the communication procedure specified in ITU Recommendation V.8, when a CM signal is detected as the response signal, and to data communicate with the transmitting modem, when a signal used in data communication is detected as the response signal.

Claim 19. (Previously Presented) The communication control apparatus according to claim 18, wherein the facsimile control signal is a DIS signal specified in ITU Recommendation T.30, and the controller executes communications with the transmitting modem based on the data communication procedure specified in ITU Recommendation V.22, when a SI signal is detected as the response signal.

Claim 20. (Previously Presented) The communication control apparatus according to claim 18, wherein the facsimile control signal is a DIS signal specified in ITU Recommendation T.30, and the controller executes communications with the transmitting modem based on the data communication procedure specified in ITU Recommendation V.32, when an AA signal is detected as the response signal.

Claim 21. (Currently Amended) A communication control apparatus provided with a receiving modem that is configured to perform transmission and reception of signals with a transmitting modem, the receiving modem ~~comprising~~; comprising:

a ~~transmitter~~ transmitter that is configured to transmit a data communication signal;

a detector that is configured to detect a response signal to the data communication signal transmitted from the transmitting modem;

a controller that is configured to communicate with the transmitting modem based on the communication procedure specified in ITU Recommendation V.8, when a CM signal is detected as the response signal.

Claim 22. (Previously Presented) The communication control apparatus according to claim 21, wherein the data communication signal is an AC signal specified in at least one of ITU Recommendation V.22 and V.23.

Claim 23. (Currently Amended) A method for controlling a communication having a receiving modem that is configured to perform a transmission and reception of signals with a transmitting modem, the method ~~comprising~~; comprising:

transmitting a facsimile control signal;

detecting a response signal to the facsimile control signal transmitted from the transmitting modem;

communicating with the transmitting modem based on the communication procedure specified in ITU Recommendation V.8, when a CM signal is detected as the response signal, and data communicating with the transmitting modem, when a signal used in data communication is detected as the response signal.

Claim 24. (Previously Presented) The method for controlling a communication having the receiving modem according to claim 23, wherein the facsimile control signal is a DIS signal specified in ITU Recommendation T.30 and the communicating executes

communications with the transmitting modem based on the data communication procedure specified in ITU Recommendation V.22, when a SI signal is detected as the response signal.

Claim 25. (Previously Presented) The method for controlling a communication having the receiving modem according to claim 23, wherein the facsimile control signal is a DIS signal specified in ITU Recommendation T.30 and the communicating executes communications with the transmitting modem based on the data communication procedure specified in ITU Recommendation V.32, when an AA signal is detected as the response signal.

Claim 26. (Currently Amended) A method for controlling a communication having a receiving modem that is configured to perform transmission and reception of signals with a transmitting modem, the method ~~comprising~~; comprising:

transmitting a data communication signal;

detecting a response signal to the data communication signal transmitted from the transmitting modem;

communicating with the transmitting modem based on the communication procedure specified in ITU Recommendation V.8, when a CM signal is detected as the response signal.

Claim 27. (Previously Presented) The method for controlling a communication having the receiving modem according to claim 26, wherein the data communication signal is an AC signal specified in at least one of ITU Recommendation V.22 and V.23.